




PROEDGE AL consists of a vast range of corner guard profiles used to protect and cover the most exposed part of any type of wall covering and existing edges. **PROEDGE AL** is made in Anodised aluminium in the size 25x25 mm. Available with self-adhesive backing. Its high impact-absorption properties ensure that it complies with compulsory EUROPEAN standards for covering chipped or hazardous edges. It is mainly used in the industrial, food and commercial sectors and where traffic is intense.

PROEDGE AL

ANODISED ALUMINIUM



PEG... 25A
PEGA 25-01A



ANODISED ALUMINIUM (gold-silver and bronze) with **ADHESIVE thermo packed** - bar length 2,7 LM - Pack. 30 Pcs - 81 LM

Article	LxH mm		
PEGAO 25A (Anod. gold)	25 x 25		
PEGAA 25A (Anod. silver)	25 x 25		
PEGAB 25A (Anod. bronze)	25 x 25		

For items without adhesive, deduct 0,70€ from the net price for LM, and write the item without the final A. E.g.: PEGAO 25

WHITE VARNISHED ALUMINIUM with **ADHESIVE thermo packed** bar length 2,7 LM - Pack. 30 Pcs - 81 LM

Article	LxH mm		
PEGA 25-01A (white varnished)	25 x 25		

COLOURS



01 - White varnished alu.

(for a precise assessment of colours and finishes, see the relative enclosed sheet)

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the necessary profile for covering the edge of the covering/wall.
2. Clean the surface on which the profile is to be laid, ensuring that it is grease-free and dry. Application is recommended at a temperature of at least 15°.
3. Remove the protective film or thermo-packaging and then also the protective paper from the adhesive.
4. Lay correctly by applying pressure evenly over the whole profile without using a hammer.